## **Product specification**

Product name	Bracket Plate W450mmXH40mmXT5mm						
ltem	Name	Symbol	SI		CGS		
Shape	Internal diameter	id	6.5	mm	0.65	cm	
	Subtitle	S	12	mm	1.2	cm	
	Width	W	450	mm	45	cm	
	Height	Н	40	mm	4	cm	
	Thickness	t	5	mm	0.5	cm	
	Pitch	Р	50	mm	5	cm	
	Quantity	Q		9			
	Screw	М	6	mm	0.6	cm	
	Direction of magnetization	М		Assiale			
	Surface treatment	Polish	-	μm			
Measuring point	Surface flux density	В	-	mT	-	G	
	Attractive force	F	-	kgf	-	gf	
	Magnetic flux density on load point	Bd	-	mT	-	G	
	Total flux	Dia o	-	Wb	-	Mx	
	Permeance coefficient	Pc	-	Pc	-		
	Operationg temperature range	Tw	100	deg C	212	deg F	
	Operationg temperature range	Tw	-	deg C	-	deg F	
Material characteristics	Material grade	Plate	3	316			
	Remanence	Br	-	mT	-	kG	
	Coericive forces	Hcb	-	kA/m	-	kOe	
	Intrisic coercivity	Hcj	-	kA/m	-	kOe	
	Maximum energy product	BH	-	kJ/m3	-	MGOe	
	Temperature	Br	-	%/deg C	-	%/deg F	
	coefficient	Hcj	-	%/deg C	-	%/deg F	
	Max. operating temperature	Tw	-	deg C	-	deg F	
	Curie temperature	Тс	-	deg C	-	deg F	
	Density	Р	-	kg/m3	-	Ŭ	
	Weight	Net	0.718	kg	718	g	
Remark	REACH RoHS Directive						

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.