

Product specification

Product name	Magnetic Filter L360mmXW350mmXH40mm Ladder			
Item	Name	Symbol	SI	CGS
Shape	Diameter	D	25 mm	2.5 cm
	Internal diameter	id	6.5 mm	0.65 cm
	Subtitle	S	12 mm	1.2 cm
	Lengh	L	360 mm	36 cm
	Width	W	350 mm	35 cm
	Height	H	40 mm	4 cm
	Thickness	T	5 mm	0.5 cm
	Pitch	P	50 mm	5 cm
	Quantity	Q	7	
	Screw	M	6 mm	0.6 cm
	Direction of magnetization	M	Assiale	
	Surface treatment	Polish	- μ m	
Measuring point	Surface flux density	B	1400 mT	14000 G
	Attractive force	F	- kgf	- gf
	Magnetic flux density on load point	Bd	- mT	- G
	Total flux	Dia o	- Wb	- Mx
	Permeance coefficient	Pc	- Pc	-
	Operationg temperature range	Tw	100 deg C	212 deg F
	Operationg temperature range	Tw	- deg C	- deg F
Material characteristics	Material grade	Magnetic Filter	316	
	Remanence	Br	- mT	- kG
	Coercive forces	Hcb	- kA/m	- kOe
	Intrinsic coercivity	Hcj	- kA/m	- kOe
	Maximum energy product	BH	- kJ/m3	- MGOe
	Temperature coefficient	Br	- %/deg C	- %/deg F
		Hcj	- %/deg C	- %/deg F
	Max. operating temperature	Tw	- deg C	- deg F
	Curie temperature	Tc	- deg C	- deg F
	Density	P	- kg/m3	-
	Weight	Net	10.137 kg	10137 g
Remark	REACH RoHS Directive			

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.