## **Product specification**

Product name	Neodymium Dia18mmX7mm					
Item	Name	Symbol	SI		CGS	
Shape	Diameter	D	18	mm	1.8	cm
	Height	Н	7	mm	0.7	cm
	Dimensional	D	0.1	mm	0.01	cm
	tolerance +/-	Н	0.1	mm	0.01	cm
	Direction of magnetization	М	Assiale			
	Surface treatment	Ni	12	μm		
Measuring point	Surface flux density	В	359.9	mΤ	3599	G
	Attractive force	F	5.27	kgf	5270	gf
	Magnetic flux density on load point	Bd	593.8	mT	5938	G
	Total flux	Dia o	0.0001511 1	Wb	15111	Mx
	Permeance coefficient	Pc	1.04	Pc	-	
	Operationg temperature range	Tw	90	deg C	194	deg F
	Operationg temperature range	Tw	-	deg C	-	deg F
Material characteristics	Material grade	Neodymium	35			
	Remanence	Br	1170-1220	mΤ	11.7-12.2	kG
	Coericive forces	Hcb	>868	kA/m	>10.9	kOe
	Intrisic coercivity	Hcj	>955	kA/m	>12	kOe
	Maximum energy product	ВН	263-287	kJ/m3	33-36	MGOe
	Temperature	Br	-0.12	%/deg C	31.78	%/deg F
	coefficient	Hcj	-0.55	%/deg C	31.01	%/deg F
	Max. operating temperature	Tw	<80	deg C	<176	deg F
	Curie temperature	Tc	310	deg C	590	deg F
	Density	Р	7.5	kg/m3	-	
	Weight	Net	0.0133	kg	13.3	g
Remark	REACH RoHS Directive					

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.