Product specification

Product name	Grip Dia25mmX120mm						
Item	Name	Symbol	!	SI		CGS	
Shape	Diameter	D	25	mm	2.5	cm	
	Subtitle	S	67	mm	6.7	cm	
	Lengh	L	120	mm	12	cm	
	Height	Н	10	mm	1	cm	
	Screw	М	6	mm	0.6	cm	
	Direction of magnetization	М	Assiale				
	Surface treatment	Polish	-	μ m			
Measuring point	Surface flux density	В	-	mΤ	-	G	
	Attractive force	F	-	kgf	-	gf	
	Magnetic flux density on load point	Bd	-	mT	-	G	
	Total flux	Dia o	-	Wb	-	Mx	
	Permeance coefficient	Рс	-	Pc	-		
	Operationg temperature range	Tw	-	deg C	-	deg F	
	Operationg temperature range	Tw	-	deg C	-	deg F	
Material characteristics	Material grade	Grip	3	316			
	Remanence	Br	-	mT	-	kG	
	Coericive forces	Hcb	-	kA/m	•	kOe	
	Intrisic coercivity	Hcj	-	kA/m	1	kOe	
	Maximum energy product	ВН	-	kJ/m3	-	MGOe	
	Temperature	Br	-	%/deg C	-	%/deg F	
	coefficient	Hcj	-	%/deg C	-	%/deg F	
	Max. operating temperature	Tw	-	deg C	-	deg F	
	Curie temperature	Tc	-	deg C	-	deg F	
	Density	Р	-	kg/m3	-		
	Weight	Net	0.378	kg	378	g	
Remark	REACH RoHS Directive						

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.