

Product specification

Product name	Magnetic Filter L250mmXW250mmXH40mm Frame/Sheath/Drawer			
Item	Name	Symbol	SI	CGS
Shape	Diameter	D	25 mm	2.5 cm
	Diameter	d	28 mm	2.8 cm
	Internal diameter	ID	27 mm	2.7 cm
	Internal diameter	id	10.5 mm	1.05 cm
	Subtitle	S	20 mm	2 cm
	Radian	R	8 mm	0.8 cm
	Lengh	L	250 mm	25 cm
	Width	W	250 mm	25 cm
	Width	w	150 mm	15 cm
	Height	H	40 mm	4 cm
	Height	h	30 mm	3 cm
	Thickness	T	5 mm	0.5 cm
	Thickness	t	10 mm	1 cm
	Pitch	P	50 mm	5 cm
	Quantity	Q	5	
	Direction of magnetization	M	Assiale	
	Surface treatment	Polish	- μ m	
Measuring point	Surface flux density	B	800 mT	8000 G
	Attractive force	F	- kgf	- gf
	Magnetic flux density on load point	Bd	- mT	- G
	Total flux	Dia o	- Wb	- Mx
	Permeance coefficient	Pc	- Pc	-
	Operating temperature range	Tw	100 deg C	212 deg F
	Operating temperature range	Tw	- deg C	- deg F
Material characteristics	Material grade	Magnetic Filter	316	
	Remanence	Br	- mT	- kG
	Coeritive forces	Hcb	- kA/m	- kOe
	Intrinsic coercivity	Hcj	- kA/m	- kOe
	Maximum energy product	BH	- kJ/m3	- MGOe
	Temperature coefficient	Br	- %/deg C	- %/deg F
		Hcj	- %/deg C	- %/deg F
	Max. operating temperature	Tw	- deg C	- deg F
	Curie temperature	Tc	- deg C	- deg F
	Density	P	- kg/m3	-
	Weight	Net	6.779 kg	6779 g
Remark	REACH RoHS Directive			

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.