

# Product specification

Product name	Lifter CSYQ300A			
Item	Name	Symbol	SI	CGS
Shape	Radian	R	155 mm	15.5 cm
	Lengh	L	162 mm	16.2 cm
	Width	W	92 mm	9.2 cm
	Height	H	91 mm	9.1 cm
	Direction of magnetization	M	Assiale	
	Surface treatment	-	- $\mu$ m	
Measuring point	Surface flux density	B	- mT	- G
	Attractive force	F	300 kgf	300000 gf
	Magnetic flux density on load point	Bd	- mT	- G
	Total flux	Dia o	- Wb	- Mx
	Permeance coefficient	Pc	- Pc	-
	Operating temperature range	Tw	- deg C	- deg F
	Operating temperature range	Tw	- deg C	- deg F
Material characteristics	Material grade	Lifter	Alnico5	
	Remanence	Br	- mT	- kG
	Coercive forces	Hcb	- kA/m	- kOe
	Intrinsic coercivity	Hcj	- kA/m	- kOe
	Maximum energy product	BH	- kJ/m3	- MGOe
	Temperature coefficient	Br	- %/deg C	- %/deg F
		Hcj	- %/deg C	- %/deg F
	Max. operating temperature	Tw	- deg C	- deg F
	Curie temperature	Tc	- deg C	- deg F
	Density	P	- kg/m3	-
	Weight	Net	7.5 kg	7500 g
Remark	-			

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.