Product specification

Item Name Symbol SI CGS Radian R 196 mm 19.6 cm Lengh L 233 mm 23.3 cm Width W 122 mm 12.2 cm Height H 118 mm 11.8 cm Direction of magnetization M Assiale Assiale Assiale Surface flux density B - mT - G Magnetic flux density Bd - mT - G Measuring point Surface flux density Bd - mT - G Measuring point On load point Dia o - Wb - Mx Permeance coefficient Pc - Pc - - - Operationg temperature range Tw - deg C - deg F - Material characteristics Material grade Lifter Alnico5	Product name	Lifter CSYQ600A						
Shape Lengh L 233 mm 23.3 cm Width W 122 mm 12.2 cm Height H 118 mm 11.2 cm Direction of magnetization M Assiale - mT - G Surface flux density B - mT - G Attractive force F 600 kgf 600000 gf Measuring point Bd - mT - G Permeance coefficient Pc - Mx Permeance coefficient Pc - Operationg temperature range Tw - deg C - deg F Material characteristics Material grade Lifter Alnico5 - - Remanence Br - mT - kGe - MGee Intrisic coercivity Hcj - kA/m - kOe - MGeg F	Item	Name	Symbol		SI		CGS	
ShapeWidthW122mm12.2cmHeightH118mm11.8cmDirection of magnetizationMAssialeSurface treatment μ mSurface flux densityB-mT-GAttractive forceF600kgf600000gfMeasuring pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-Material gradeLifterAlnico5-deg FMaterial gradeLifterAlnico5-kGCoercive forcesHcb-kA/m-Material characteristicsTemperatureBr-mT-Material characteristicsTemperatureBr-%/deg C-Material characteristicsTemperatureTr-kGMaterial characteristicsTemperatureBr-%/deg C-Material characteristicsTemperatureTr-deg C-Material characteristicsTemperatureTr-deg C-Material characteristicsTemperatureTr-deg C-Material characteristicsTemperatureTr-deg C-Material characteristicsTemperatureTr<	Shape	Radian	R	196	mm	19.6	cm	
ShapeHeightH118mm11.8cmDirection of magnetizationMAssialeSurface treatment μ mSurface flux densityB-mT-Attractive forceF600kgf600000Magnetic flux densityBd-mT-On load pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-Operationg temperature rangeTw-deg C-Material characteristicsMaterial gradeLifterAlnico5Material characteristicsMaximum energy productBH-kJ/m3-Material characteristicsTemperature CoeficientBr-%/deg C-Material characteristicsBr-kJ/m3-MGOeMaterial characteristicsTemperature CoeficientBr-%/deg C-Material characteristicsTemperature CoeficientTw-deg C-Material characteristicsTemperature CoeficientTw-deg C-Maxinum energy productBH-kJ/m3-MGOeMaxinum energy temperatureTw-deg C-deg FMax. operating temperatureTw-deg C		Lengh	L	233	mm	23.3	cm	
Direction of magnetizationMAssialeSurface treatment μ mSurface flux densityB-mT-Attractive forceF600kgf600000gfMagnetic flux density on load pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-deg FOperationg temperature rangeTw-deg C-deg FMaterial gradeLifterAlnico5-KGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeTemperature coefficientHcj-%/deg C-%/deg FMax, operating temperatureTw-deg C-%/deg FMax, operating temperatureTw-deg C-%/deg FMax, operating temperatureTw-deg C-%/deg FMax, operating temperatureTw-deg C-%/deg FDensityP-kg/m3MGOeMax, operating temperatureTw-deg C-deg FDensityP-kg/m3WeightNet23		Width	W	122	mm	12.2	cm	
Material characteristicsMAssuleMaterial characteristics- μ m-Surface treatment μ m-Surface flux density Attractive forceB-mT-GAttractive forceF600kgf600000gfMagnetic flux density on load pointBd-mT-GMeasuring pointTotal fluxDia o-Wb-MxPermeance coefficientPc-PcOperationg temperature rangeTw-deg C-deg FOperationg temperature rangeTw-deg C-deg FMaterial gradeLifterAlnico5deg FRemanenceBr-mT-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-%/deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FDensityP-kg/m3-MGOeMax. operating temperatureTw-deg C-%/deg FMax. operating temperatureTw-deg C-deg FDensityP-kg/m3		Height	Н	118	mm	11.8	cm	
Measuring pointSurface flux density Attractive forceB-mT-GMeasuring pointMagnetic flux density on load pointBd-mT-GMagnetic flux density on load pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-Operationg temperature rangeTw-deg C-Material characteristicsMaterial gradeLifterAlnico5Material characteristicsMaterial gradeHcb-kA/mMaterial characteristicsTemperature meratureBH-kJ/m3-Material characteristicsTemperature meratureBr-%/deg C-Material characteristicsTemperature meratureBr-%/deg C-Material characteristicsTemperature meratureTr-deg C-Material characteristicsTemperature meratureTr-deg C-Material characteristicsTemperature meratureTr-deg C-Material characteristicsTemperature meratureTr-deg C-Material characteristicsTemperature meratureTr-deg C-Material characteristicsTemperature meratureTr-deg C <td></td> <td>М</td> <td colspan="4">Assiale</td>			М	Assiale				
Measuring pointAttractive forceF600kgf600000gfMagnetic flux density on load pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-Operationg temperature rangeTw-deg C-Operationg temperature rangeTw-deg C-Material gradeLifterAlnico5-deg FMaterial gradeLifterAlnico5-kGCoercicive forcesHcb-kA/m-Intrisic coercivityHcj-kA/m-Maximum energy productBH-%/deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-OpensityP-kg/m3-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating temperatureTw-deg C-Max. operating tem		Surface treatment	-	-	μm			
Measuring pointMagnetic flux density on load pointBd-mT-GTotal fluxDia o-Wb-MxPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-Operationg temperature rangeTw-deg C-Material gradeLifterAlnico5RemanenceBr-mT-RemanenceBr-kA/m-Material characteristicsGoercive forcesHcb-kA/mMaterial characteristicsTemperatureBr-%/deg C-Material characteristicsTemperatureBr-%/deg C-Material characteristicsTemperatureTrw-deg C-Material characteristicsDensityP-%/deg C-Material characteristicsMax. operating temperatureTrw-deg C-Max. operating temperatureTrw-deg C-%/deg FDensityP-kg/m3WeightNet23kg23000g	Measuring point	Surface flux density	В	-	mT	-	G	
Measuring pointImage: Discrete for the second s		Attractive force	F	600	kgf	600000	gf	
Measuring pointPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-deg FOperationg temperature rangeTw-deg C-deg FMaterial gradeLifterAlnico5-deg FRemanenceBr-mT-kGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeTemperature coefficientBr-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FOurie temperatureTc-deg C-deg FOurie temperatureTc-deg C-%/deg FOperating temperatureTw-deg C-deg FOperating temperatureTw-deg C-deg FOperating temperatureTw-deg C-deg FOperating temperatureTw-deg C-deg FOperating temperatureTc-deg C-deg FOperating temperatureTc-deg C-deg FOperating temperatureTc-deg C-deg FOperating temperatureP-kg/m3-Operating temperatureNet2			Bd	-	mT	-	G	
Material characteristicsPermeance coefficientPc-Pc-Operationg temperature rangeTw-deg C-deg FOperationg temperature rangeTw-deg C-deg FMaterial gradeLifterAlnico5deg FRemanenceBr-mT-kGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeTemperatureBr-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FOurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g-		Total flux	Dia o	-	Wb	-	Mx	
Itemperature rangeIW-deg C-deg FOperationg temperature rangeTw-deg C-deg FMaterial gradeLifterAlnico5RemanenceBr-mT-kGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeTemperatureBr-%/deg C-%/deg FCoefficientHcj-%/deg C-deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g		Permeance coefficient	Pc	-	Pc	-		
temperature rangeIW-deg C-deg FMaterial gradeLifterAlnico5RemanenceBr-mT-kGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaterial characteristicsTemperatureBr-kJ/m3-MGOeMaximum energy productBH-kJ/m3-MGOeMaximum energy productBr-%/deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FMax. operating temperatureTw-deg C-deg FDensityP-kg/m3WeightNet23kg23000g		, s	Tw	-	deg C	-	deg F	
Material gradeLifterAlnico5RemanenceBr-mT-kGCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeMaximum energy productBH-%/deg C-%/deg FMaximum energy productBr-%/deg C-%/deg FMax. operature coefficientHcj-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g-			Tw	-	deg C	-	deg F	
Material characteristicsCoericive forcesHcb-kA/m-kOeIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeMaximum energy productBH-%/deg C-%/deg FCoefficientHcj-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g			Lifter	Alr	Alnico5			
Material characteristicsIntrisic coercivityHcj-kA/m-kOeMaximum energy productBH-kJ/m3-MGOeTemperature coefficientBr-%/deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g		Remanence	Br	-	mT	-	kG	
Material characteristicsMaximum energy productBH-kJ/m3-MGOeTemperature coefficientBr-%/deg C-%/deg FMax. operating temperatureTw-deg C-%/deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g		Coericive forces	Hcb	-	kA/m	-	kOe	
Material characteristicsproductBH-KJ/m3-MGOeTemperature coefficientBr-%/deg C-%/deg FMax. operating temperatureTw-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3-WeightNet23kg23000g		Intrisic coercivity	Hcj	-	kA/m	-	kOe	
characteristicsTemperature coefficientBr-%/deg C-%/deg FMax. operating temperatureTw-%/deg C-%/deg FCurie temperatureTw-deg C-deg FDensityP-deg C-deg FWeightNet23kg23000g			BH	-	kJ/m3	-	MGOe	
coefficientHcj-%/deg C-%/deg FMax. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g		Temperature	Br	-	%/deg C	-	%/deg F	
Max. operating temperatureTw-deg C-deg FCurie temperatureTc-deg C-deg FDensityP-kg/m3WeightNet23kg23000g			Hcj	-		-	%/deg F	
Curie temperatureTc-deg C-deg FDensityP-kg/m3-WeightNet23kg23000g			Tw	-		-	deg F	
DensityP-kg/m3-WeightNet23kg23000g		· · · · · · · · · · · · · · · · · · ·	Tc	-	deg C	-	deg F	
Weight Net 23 kg 23000 g		Density	Р	-	-	-	-	
			Net	23	_	23000	g	
	Remark			-				

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.