

Product specification

Product name	Rubber Magnet Sheet t2mmX500mmX10M			
Item	Name	Symbol	SI	CGS
Shape	Lengh	L	10000 mm	1000 cm
	Width	W	500 mm	50 cm
	Height	H	2 mm	0.2 cm
	Direction of magnetization	M	Assiale	
	Surface treatment	UV Oil	- μ m	
Measuring point	Surface flux density	B	- mT	- G
	Attractive force	F	- kgf	- gf
	Magnetic flux density on load point	Bd	- mT	- G
	Total flux	Dia o	- Wb	- Mx
	Permeance coefficient	Pc	- Pc	-
	Operating temperature range	Tw	80 deg C	176 deg F
	Operating temperature range	Tw	- deg C	- deg F
Material characteristics	Material grade	Rubber Magnet Sheet	異方性	
	Remanence	Br	- mT	- kG
	Coeritive forces	Hcb	- kA/m	- kOe
	Intrinsic coercivity	Hcj	- kA/m	- kOe
	Maximum energy product	BH	- kJ/m3	- MGOe
	Temperature coefficient	Br	- %/deg C	- %/deg F
		Hcj	- %/deg C	- %/deg F
	Max. operating temperature	Tw	- deg C	- deg F
	Curie temperature	Tc	- deg C	- deg F
	Density	P	- kg/m3	-
	Weight	Net	- kg	- g
Remark	-			

Information on these magnetic characteristics are approximate and reference values. When using the calculated values for actual magnetic application products and research and development of the application of magnetic products, use these values as reference values. We are not responsible for the results from the reference values. The details can be found by referring to the product specifications. All specifications are subject to change without notice.